INDEX TO

EXPERIMENTAL MECHANICS

Volume 31, 1991

TITLE INDEX

Active Vibration Damping of a Planar Truss Using Air-jet Thrusters — W.L. Hallauer, Jr., S.E. Lamberson and C.A. Baer, 189-196 (Sept.).

Assessment of Flow Stress and Plastic Strain by Spectrum Analysis — Y.Z. Dai and F.P. Chiang, 197-201 (Sept.).

Axial Load Capacity of Cylindrical Shells with Local Geometric Defects — S. Krishnakumar and C.G. Foster, 104-110 (June).

Combining Photoelasticity and Finite-element Methods for Stress Analysis Using Least Squares — D.G. Berghaus, 36-41 (Mar.).

Comparison of Boundary and Global Collocation Solutions for K_I and CMOD Calibration Functions, A — R.J. Sanford and M.T. Kirk, 52-59 (Mar.).

Contact Force Prediction and Experimental Verification of an OHC Finger-follower-type Cam-valve System — W.-J. Kim, H.-S. Jeon and Y.-S. Park, 150-156 (June).

Contouring by Moiré Interferometry — Y.Z. Dai and F.P. Chiang, 76-81 (Mar.).

Crack-growth-rate Estimation in a Three-point Bend Specimen During Low-cycle Fatigue — J. Tryding, 42-46 (Mar.).

Designing an All-purpose Force Transducer — S.A. Masroor and L.W. Zachary, 33-35 (Mar.).

Determination of Fracture Parameters Using Embedded Fiber-optic Sensors—N. Narendran, A. Shukla and S.V. Letcher, 360-365 (Dec.).

Determination of the Plastic Zone by Laser-speckle Correlation — Y.Z. Dai, C.J. Tay and F.P. Chiang, 348-352 (Dec.).

Determining the Three Individual Stress Components from Measured Isochromatic Fringes — Y.M. Huang, C.H Lin, J.C. Suhling, and R.E. Rowlands, 310-318 (Dec.).

Development of a Load-cell Compensation System — M.J. Dixon, 21-24 (Mar.).

Diffraction Theory of Optical Interference Moiré and a Device for Production of Variable Virtual Reference Gratings: A Moiré Microscope — T.W. Shield and K.-S. Kim, 126-134 (June).

Direct-tension Split Hopkinson Bar for High Strain-rate Testing, A — G.H. Staab and A. Gilat, 232-235 (Sept.).

Displacement and Strain Measurement with Automated Grid Methods — J.S. Sirkis and T.J. Lim, 382-388 (Dec.).

Dynamic Fracture Analysis by Moiré Interferometry — K. Arakawa, R.H. Drinnon, Jr., M. Kosai and A.S. Kobayashi, 306-309 (Dec.).

Dynamic Structural Loading Using a Light Gas Gun — F.Y. Sorrell and M.D. Smith, 157-162 (June).

Experimental Investigation of Iosipescu Specimen for Composite Materials, An — H. Ho, M.Y. Tsai, J. Morton and G.L. Farley, 328-337 (Dec.).

Experimental Validation of Load Distribution in Screw Threads, An — M. D'Eramo and P. Cappa, 70-75 (Mar.).

Fracture-toughness Tests and Displacement and Crack-stability Analyses of Tungsten Round Bend Specimens — J.H. Underwood, F.I. Baratta and J.J. Zalinka, 353-359 (Dec.).

Full-field Representation of Discretely Sampled Surface Deformation for Displacement and Strain Analysis -- M.A. Sutton, J.L. Turner, H.A. Bruck and T.A. Chae, 168-177 (June).

Fully Automatic Stress-analysis System by Using Electro-optic Modulation, A — Y.P. Zhang, 344-347 (Dec.).

Fundamental Study on Rupture by Low-cycle Fatigue of Polymers Applying the Fine-grid Method — A. Shimamoto, S. Takahashi and A. Yokota, 65-69 (Mar.).

Holographic Investigation of the Expansion-control Characteristics of Steel Inserts in Pistons — M.M. Ratnam and W.T. Evans, 319-327 (Dec.).

Holographic Moiré for Strain Fringe Patterns, The — J. Fang and F.-L. Dai, 163-167 (June).

Hydroelastic Reduced Scale Model for Wave-loaded Compliant Tower — R.C. Batista, E.M.L. Carvalho and N. Roitman, 220-225 (Sept.).

Impact of Fruit on Flexible Beams to Sense Modulus of Elasticity — J.K. Schueller and T.M.P. Wall, 118-121 (June).

Influence of Specimen Gage Length and Loading Method on the Axial Compressive Strength of a Unidirectional Composite Material — D.F. Adams and E.Q. Lewis, 14-20 (Mar.).

Laser Diffraction Methods for High-temperature Strain Measurements — H. Pih and K.C. Liu, 60-64 (Mar.).

Laser Speckle Decorrelation as a Noncontact Method for Brittle-ductile Fracture Differentiation — J.S. Steckenrider and J.W. Wagner, 8-13 (Mar.).

Logical Moiré and Its Application — A. Asundi and K.H. Yung, 236-242 (Sept.).

Long Wavelength Impact of Izod Fracture Specimens: An Experimental/Numerical Investigation — H.Y. Jung, J.S. Epstein, V.A. Deason and W.G. Reuter, 281-287 (Sept.).

Measurement of Axisymmetric Prebuckling Defomations in Axially Compressed Cylindrical Shells — S. Krishnakumar and C.G. Foster, 47-51 (Mar.).

Measurement of Stress-intensity Factor by Means of A-C Potential Drop Technique — M. Saka, M. Nakayama, T. Kaneko and H. Abe, 209-212 (Sept.).

Microhardness Indentation Application and Limitation in Fracture-toughness Evaluation of Ceramics — H. Nayeb-Hashemi and C.A. Tracy, 366-372 (Dec.).

Micro-interferometry for Measurement of Thermal Displacements at Fiber/Matrix Interfaces — N.R. Sottos, W.R. Scott and R.L. McCullough, 98-103 (June).

Microscopic Mapping of Subnanometric Motion in Semitransparent Systems — H. Lin, M. Sharnoffand L. Du, 257-263 (Sept.).

Misalignment Sensitivity Test for Load Cells — R.A. Mitchell, 140-143 (June).

Moiré Interferometry: Advances and Applications — D. Post, 276-280 (Sept.).

Moiré Interferometry Determination of Residual Stresses in the Presence of Gradients — G. Nicoletto, 252-256 (Sept.).

Multiple Geometric Defects: Their Effect on Stability of Cylindrical Shells — S. Krishnakumar and C.G. Foster, 213-219 (Sept.).

New Developments in the Localized Hybrid Method of Stress Analysis — M.Y. Tsai and J. Morton, 298-305 (Dec.).

New Technique for the Prediction of Buckling Loads from Nondestructive Vibration Tests, A — M.A. Souza and L.M.B. Assaid, 93-97 (June).

Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures — P.L. Fuhr, D. Huston, J.G. Beliveau, P.J. Kajensk and W.B. Spillman, 185-188 (June).

Out-of-plane Deflections of Metallic and Composite Pin-loaded Coupons — S.M. Serabian and R.F. Anastasi, 25-32 (Mar.).

Passenger Air-bag Study Using Geometric Analysis of Rigid-body Motion — G.S. Nusholtz, J. Wu and P. Kaiker, 264-270 (Sept.).

Phase-stepped Fractional Moiré — J.H. Sullivan, 373-381 (Dec.).

Photoelastic and FEM Analysis of Interfacial Crack Propagation, A — I. Miskioglu, C.R. Villmann, J.S. Pawloski and D.M. Pariseau, 135-139 (June).

Photoelastic Study of Friction at Multipoint Contacts, A — J.W. Dally and Y.-M. Chen, 144-149 (June).

Photomechanical Behavior of Cellulose Acetate Under Viscoelastoplastic Deformation — S. Tadano and H. Ishikawa, 226-231 (Sept.).

Plastic Buckling of Cylindrical Shells Under Biaxial Loading — J.J. Giezen, C.D. Babcock and J. Singer, 337-343 (Dec.).

Quasi-static and Dynamic Crack Growth Along Bimaterial Interfaces: A Note on Crack-tip Field Measurements Using Coherent Gradient Sensing — H.V. Tippur and A.J. Rosakis, 243-251 (Sept.).

Reduction of Contact Stress by Use of Relief Notches — M. Bijak-Zochowski, A.M. Waas, W.J. Anderson and C.E. Miniatt, 271-275 (Sept.).
Simulation of Voids Effects on Ductile Fracture of Metallic Alloys — A. El-Domiaty and M. Shaker, 293-297 (Dec.).
Small-crack Closure Measurements in Titanium Alloys — J.M. Larsen and J.R. Jira, 82-87 (Mar.).
Strength and Stiffness of Sandwich Beams in Bending — K. Lingaiah and B.G. Suranarayana, 1-7 (Mar.).
Stress Analysis of Thin Polyimide Films Using Holographic Interferometry — M.A. Maden and R.J. Farris, 178-184 (June).
Tests on the Ductility of Asymmetric Part-through Center Cracks in Plates — G.A. Kardomateas, 288-292 (Sept.).
Thermal Stress Analysis of a Silicon Carbide/Aluminum Composite — E.E. Gdoutos, D. Karalekas and I.M. Daniel, 202-208 (Sept.).
Use of Electrical-resistance Metallic Foil Strain Gages for Measuring Large Dynamic Plastic Deformation, On the — S. Huang and A.S. Khan 122-125 (June).
Viscoelastic Response of a Unidirectional Composite Containing Two Viscoelastic Constituents — D.E. Walrath, 111-117 (June).
Zero-shift Values of Automatic and Inexpensive Strain-gage Instrumentation Systems — P. Cappa, K.G. McConnell and L.W. Zachary, 88-92 (Mar.).

AUTHOR INDEX

Abe, H. — Measurement of Stress-intensity Factor by Means of A-C Potential Drop Technique, 209-212 (Sept.).

Adams, D.F. — Influence of Specimen Gage Length and Loading Method on the Axial Compressive Strength of a Unidirectional Composite Material, 14-20 (Mar.).

Anastasi, R.F. — Out-of-plane Deflections of Metallic and Composite Pin-loaded Coupons, 25-32 (Mar.).

Anderson, W.J. — Reduction of Contact Stress by Use of Relief Notches, 271-275 (Sept.).

Arakawa, K. — Dynamic Fracture Analysis by Moiré Interferometry, 306-309 (Dec.).

Assaid, L.M.B. — A New Technique for the Prediction of Buckling Loads from Nondestructive Vibration Tests, 93-97 (June).

Asundi, A. — Logical Moiré and Its Application, 236-242 (Sept.).

Babcock, C.D. — Plastic Buckling of Cylindrical Shells Under Biaxial Loading, 337-343 (Dec.).

Baer, C.A. — Active Vibration Damping of a Planar Truss Using Air-jet Thrusters, 189-196 (Sept.).

Baratta, F.I. — Fracture Toughness Tests and Displacement and Crack-stability Analyses of Tungsten Round Bend Specimens, 353-359 (Dec.).

Batista, R.C. — Hydroelastic Reduced Scale Model for Wave-loaded Compliant Tower, 220-225 (Sept.).

Beliveau, J.G. — Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures,185-188 (June).

Berghaus, D.G. — Combining Photoelasticity and Finite-element Methods for Stress Analysis Using Least Squares, 36-41 (Mar.).

Bijak-Zochowski, M. — Reduction of Contact Stress by Use of Relief Notches, 271-275 (Sept.).

Bruck, H. — Full-field Representation of Discretely Sampled Surface Deformation for Displacement and Strain Analysis, 168-177 (June).

Cappa, P. — An Experimental Validation of Load Distribution in Screw Threads, 70-75 (Mar.).
Zero-shift Values of Automatic and Inexpensive Strain-gage Instrumentation Systems, 88-92 (Mar.).

Carvalho, E.M.L. — Hydroelastic Reduced Scale Model for Wave-loaded Compliant Tower, 220-225 (Sept.).

Chae, T.A. — Full-field Representation of Discretely Sampled Surface Deformation for Displacement and Strain Analysis, 168-177 (June).

Chen, Y.M. — A Photoelastic Study of Friction at Multipoint Contacts, 144-149 (June).

Chiang, F.P. — Contouring by Moiré Interferometry, 76-81 (Mar.).
Assessment of Flow Stress and Plastic Strain by Spectrum Analysis, 197-201 (Sept.).
Determination of the Plastic Zone by Laser Speckle Correlation, 348-352 (Dec.).

D'Eramo, M. — An Experimental Validation of Load Distribution in Screw Threads, 70-75 (Mar.).

Dai, F.-L. — The Holographic Moiré for Strain Fringe Patterns, 163-167 (June).

Dai, Y.Z. — Contouring by Moiré Interferometry, 76-81 (Mar.).
Assessment of Flow Stress and Plastic Strain by Spectrum Analysis, 197-201 (Sept.).
Determination of the Plastic Zone by Laser-speckle Correlation, 348-352 (Dec.).

Dally, J.W. — A Photoelastic Study of Friction at Multipoint Contacts, 144-149 (June).

Daniel, I.M. — Thermal Stress Analysis of a Silicon Carbide/Aluminum Composite, 202-208 (Sept.).

Deason, V.A. — Long Wavelength Impact of Izod Fracture Specimens: An Experimental/Numerical Investigation, 281-287 (Sept.).

Dixon, M.J. — Development of a Load-cell Compensation System, 21-24 (Mar.).

Drinnon, Jr., R.H. — Dynamic Fracture Analysis by Moiré Interferometry, 306-309 (Dec.).

Du, L. — Microscopic Mapping of Subnanometric Motion in Semi-transparent Systems, 257-263 (Sept.).

El-Domiaty, A. — Simulation of Voids Effects on Ductile Fracture of Metallic Alloys, 293-297 (Dec.).

Epstein, J.S. — Long Wavelength Impact of Izod Fracture Specimens: An Experimental/Numerical Investigation, 281-287 (Sept.).

Evans, W.T. — Holographic Investigation of the Expansion-control Characteristics of Steel Inserts in Pistons, 319-327 (Dec.).

Fang, J. — The Holographic Moiré for Strain Fringe Patterns, 163-167 (June).

Farley, G.L. — An Experimental Investigations of Iosipescu Specimen for Composite Materials, 328-337 (Dec.).

Farris, R.J. — Stress Analysis of Thin Polyimide Films Using Holographic Interferometry, 178-184 (June).

Foster, C.G. — Measurement of Axisymmetric Prebuckling Deformations in Axially Compressed Cylindrical Shells, 47-51 (Mar.).
Axial Load Capacity of Cylindrical Shells with Local Geometric Defects, 104-110 (June).
Multiple Geometric Defects: Their Effect on Stability of Cylindrical Shells, 213-219 (Sept.).

Fuhr, P.L. — Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures, 185-188 (June).

Gdoutos, E.E. — Thermal Stress Analysis of a Silicon Carbide/Aluminum Composite, 202-208 (Sept.).

Giezen, J.J. — Plastic Buckling of Cylindrical Shells Under Biaxial Loading, 337-343 (Dec.).

Gilat, A. — A Direct-tension Split Hopkinson Bar for High Strain-rate Testing, 232-235 (Sept.).

Hallauer, Jr., W.L. — Active Vibration Damping of a Planar Truss Using Air-jet Thrusters, 189-196 (Sept.).

Ho, H. — An Experimental Investigation of Iosipescu Specimen for Composite Materials, 328-337 (Dec.).

Huang, S. — On the Use of Electrical-resistance Metallic Foil Strain Gages for Measuring Large Dynamic Plastic Deformation, 122-125 (June).

Huang, Y.M. — Determining the Three Individual Stress Components from Measured Isochromatic Fringes, 310-318 (Dec.).

Huston, D. — Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures, 185-188 (June).

Ishikawa, H. — Photomechanical Behavior of Cellulose Acetate Under Viscoelastoplastic Deformation, 226-231 (Sept.).

Jeon, H.-S. — Contact Force Prediction and Experimental Verification of an OHC Finger-follower-type Cam-valve System, 150-156 (June).

Jira, J.R. — Small-crack Closure Measurements in Titanium Alloys, 82-87 (Mar.).

Jung, H.Y. — Long Wavelength Impact of Izod Fracture Specimens: An Experimental/Numerical Investigation, 281-287 (Sept.).

Kaiker, P. — Passenger Air-bag Study Using Geometric Analysis of Rigid-body Motion, 264-270 (Sept.).

Kajensk, P.J. — Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures, 185-188 (June).

Kaneko, T. — Measurement of Stress-intensity Factor by Means of A-C Potential Drop Technique, 209-212 (Sept.).

Karalekas, D. — Thermal Stress Analysis of a Silicon Carbide/Aluminum Composite, 202-208 (Sept.).

Kardomateas, G.A. — Tests on the Ductility of Asymmetric Part-through Center Cracks in Plates, 288-292 (Sept.).

Khan, A.S. — On the Use of Electrical-resistance Metallic Foil Strain Gages for Measuring Large Dynamic Plastic Deformation, 122-125 (June).
Kim, W.-J. — Contact Force Prediction and Experimental Verification of an OHC Finger-follower-type Cam-valve System, 150-156 (June).
Kim, K.-S. — Diffraction Theory of Optical Interference Moiré and a Device for Production of Variable Virtual Reference Gratings: A Moiré Microscope, 126-134 (June).
Kirk, M.T. — A Comparison of Boundary and Global Collocation Solutions for K_I and CMOD Calibration Functions, 52-59 (Mar.).
Kobayashi, A.S. — Dynamic Fracture Analysis by Moiré Interferometry, 306-309 (Dec.).
Kosai, M. — Dynamic Fracture Analysis by Moiré Interferometry, 306-309 (Dec.).
Krishnakumar, S. — Measurement of Axisymmetric Prebuckling Deformations in Axially Compressed Cylindrical Shells, 47-51 (Mar.).
Axial Load Capacity of Cylindrical Shells with Local Geometric Defects, 104-110 (June).
Multiple Geometric Defects: Their Effect on Stability of Cylindrical Shells, 213-219 (Sept.).
Lamberson, S.E. — Active Vibration Damping of a Planar Truss Using Air-jet Thrusters, 189-196 (Sept.).
Larsen, J.M. — Small-crack Closure Measurements in Titanium Alloys, 82-87 (Mar.).
Lechter, S.V. — Determination of Fracture Parameters Using Embedded Fiber-optic Sensors, 360-365 (Dec.).
Lewis, E.Q. — Influence of Specimen Gage Length and Loading Method on the Axial Compressive Strength of a Unidirectional Composite Material, 14-20 (Mar.).
Lim, J.T. — Displacement and Strain Measurement with Automated Grid Methods, 382-388 (Dec.).
Lin, C.H. — Determining the Three Individual Stress Components from Measured Isochromatic Fringes, 310-318 (Dec.).
Lin, H. — Microscopic Mapping of Subnanometric Motion in Semitransparent Systems, 257-263 (Sept.).
Lingaiah, K. — Strength and Stiffness of Sandwich Beams in Bending, 1-7 (Mar.).
Liu, K.C. — Laser Diffraction Methods for High-temperature Strain Measurements, 60-64 (Mar.).
Maden, M.A. — Stress Analysis of Thin Polyimide Films Using Holographic Interferometry, 178-184 (June).
Masroor, S.A. — Designing an All-purpose Force Transducer, 33-35 (Mar.).
McConnell, K.G. — Zero-shift Values of Automatic and Inexpensive Strain-gage Instrumentation Systems, 88-92 (Mar.).
McCullough, R.L. — Micro-interferometry for Measurement of Thermal Displacements at Fiber/Matrix Interfaces, 98-103 (June).
Miniatt, C.E. — Reduction of Contact Stress by Use of Relief Notches, 271-275 (Sept.).
Miskioglu, I. — A Photoelastic and FEM Analysis of Interfacial Crack Propagation, 135-139 (June).
Mitchell, R.A. — Misalignment Sensitivity Test for Load Cells, 140-143 (June).
Morton, J. — New Developments in the Localized Hybrid Method of Stress Analysis, 298-305 (Dec.).
An Experimental Investigation of Iosipescu Specimen for Composite Materials, 328-337 (Dec.).
Nakayama, M. — Measurement of Stress-intensity Factor by Means of A-C Potential Drop Technique, 209-212 (Sept.).
Narendran, N.—Determination of Fracture Parameters Using Embedded Fiber-optic Sensors, 360-365 (Dec.).
Nayeb-Hashemi, H. — Microhardness Indentation Application and Limitation in Fracture-toughness Evaluation of Ceramics, 366-372 (Dec.).
Nicoletto, G. — Moiré Interferometry Determination of Residual Stresses in the Presence of Gradients, 252-256 (Sept.).
Nusholtz, G.S. — Passenger Air-bag Study Using Geometric Analysis of Rigid-body Motion, 264-270 (Sept.).
Pariseau, D.M. — A Photoelastic and FEM Analysis of Interfacial Crack Propagation, 135-139 (June).
Park, Y.-S. — Contact Force Prediction and Experimental Verification of an OHC Finger-follower-type Cam-valve System, 150-156 (June).
Pawloski, J.S. — A Photoelastic and FEM Analysis of Interfacial Crack Propagation, 135-139 (June).
Pih, H. — Laser Diffraction Methods for High-temperature Strain Measurements, 60-64 (Mar.).
Post, D. — Moiré Interferometry: Advances and Applications, 276-280 (Sept.).
Ratnam, M.M. — Holograhic Investigation of the Expansion-control Characteristics of Steel Inserts in Pistons, 319-327 (Dec.).
Reuter, W.G. — Long Wavelength Impact of Izod Fracture Specimens: An Experimental/Numerical Investigation, 281-287 (Sept.).
Roitman, N. — Hydroelastic Reduced Scale Model for Wave-loaded Compliant Tower, 220-225 (Sept.).
Rosakis, A.J. — Quasi-static and Dynamic Crack Growth Along bimaterial Interfaces: A Note on Crack-tip Field Measurements Using Coherent Gradient Sensing, 243-251 (Sept.).
Rowlands, R.E. — Determining the Three Individual Stress Components from Measured Isochromatic Fringes, 310-318 (Dec.).
Saka, M. — Measurement of Stress-intensity Factor by Means of A-C Potential Drop Technique, 209-212 (Sept.).
Sanford, R.J. — A Comparison of Boundary and Global Collocation Solutions for K_I and CMOD Calibration Functions, 52-59 (Mar.).
Schueller, J.K. — Impact of Fruit on Flexible Beams to Sense Modulus of Elasticity, 118-121 (June).
Scott, W.R. — Micro-interferometry for Measurement of Thermal Displacements at Fiber/Matrix Interfaces, 98-103 (June).
Serabian, S.M. — Out-of-plane Deflections of Metallic and Composite Pin-loaded Coupons, 25-32 (Mar.).
Shaker, M. — Simulation of Voids Effects on Ductile Fracture of Metallic Alloys, 293-297 (Dec.).
Sharnoff, M. — Microscopic Mapping of Subnanometric Motion in Semitransparent Systems, 257-263 (Sept.).
Shield, T.W. — Diffraction Theory of Optical Interference Moiré and a Device for Production of Variable Virtual Reference Gratings: A Moiré Microscope, 126-134 (June).
Shimamoto, A. — Fundamental Study on Rupture by Low-cycle Fatigue of Polymers Applying the Fine-grid Method, 65-69 (Mar.).
Shukla, A. — Determination of Fracture Parameters Using Embedded Fiber-optic Sensors, 360-365 (Dec.).
Singer, J. — Plastic Buckling of Cylindrical Shells Under Biaxial Loading, 337-343 (Dec.).
Sirkis, J.S. — Displacement and Strain Measurement with Automated Grid Methods, 382-388 (Dec.).
Smith, M.D. — Dynamic Structural Loading Using a Light Gas Gun, 157-162 (June).
Sorrell, F.Y. — Dynamic Structural Loading Using a Light Gas Gun, 157-162 (June).
Sottos, N.R. — Micro-interferometry for Measurement of Thermal Displacements at Fiber/Matrix Interfaces, 98-103 (June).
Souza, M.A. — A New Technique for the Prediction of Buckling Loads from Nondestructive Vibration Tests, 93-98 (June).
Spillman, W.B. — Optical Noncontact Dual-angle Linear Displacement Measurements of Large Structures, 185-188 (June).
Staab, G.H. — A Direct-tension Split Hopkinson Bar for High Strain-rate Testing, 232-235 (Sept.).
Steckenrider, J.S. — Laser Speckle Decorrelation as a Noncontact Method for Brittle-ductile Fracture Differentiation, 8-13 (Mar.).
Suhling, J.C. — Determining the Three Individual Stress Components from Measured Isochromatic Fringes, 310-318 (Dec.).
Sullivan, J.H. — Phase-stepped Fractional Moiré, 373-381 (Dec.).
Suranarayana, B.G. — Strength and Stiffness of Sandwich Beams in Bending, 1-7 (Mar.).
Sutton, M. — Full-field Representation of Discretely Sampled Surface Deformation for Displacement and Strain Analysis, 168-177 (June).
Tadano, S. — Photomechanical Behavior of Cellulose Acetate Under Viscoelastoplastic Deformation, 226-231 (Sept.).
Takahashi, S. — Fundamental Study on Rupture by Low-cycle Fatigue of Polymers Applying the Fine-grid Method, 65-69 (Mar.).
Tay, C.J. — Determination of the Plastic Zone by Laser Speckle Correlation, 348-352 (Dec.).
Tippur, H.V. — Quasi-static and Dynamic Crack Growth Along Bimaterial Interfaces: A Note on Crack-tip Field Measurements Using Coherent Gradient Sensing, 243-251 (Sept.).
Tracy, C.A. — Microhardness Indentation Application and Limitation in Fracture-toughness Evaluation of Ceramics, 366-372 (Dec.).
Tryding, J. — Crack-growth-rate Estimation in a Three-point Bend Specimen During Low-cycle Fatigue, 42-46 (Mar.).
Tsai, M.Y. — New Developments in the Localized Hybrid Method of Stress Analysis, 298-305 (Dec.).
An Experimental Investigation of Iosipescu Specimen for Composite Materials, 328-337 (Dec.).

Turner, J.L. — Full-field Representation of Discretely Sampled Surface Deformation for Displacement and Strain Analysis, 168-177 (June).
Underwood, J.H. — Fracture-toughness Tests and Displacement and Crack-stability Analyses of Tungsten Round Bend Specimens, 353-359 (Dec.).
Villmann, C.R. — A Photoelastic and FEM Analysis of Interfacial Crack Propagation, 135-139 (June).
Waas, A.M. — Reduction of Contact Stress by Use of Relief Notches, 271-275 (Sept.).
Wagner, J.W. — Laser Speckle Decorrelation as a Noncontact Method for Brittle-ductile Fracture Differentiation, 8-13 (Mar.).
Wall, T.M.P. — Impact of Fruit on Flexible Beams to Sense Modulus of Elasticity, 118-121 (June).
Walrath, D.E. — Viscoelastic Response of a Unidirectional Composite Containing Two Viscoelastic Constituents, 111-117 (June).
Wu, J. — Passenger Air-bag Study Using Geometric Analysis of Rigid-body Motion, 264-270 (Sept.).
Yokota, A. — Fundamental Study on Rupture by Low-cycle Fatigue of Polymers Applying the Fine-grid Method, 65-69 (Mar.).
Yung, K.H. — Logical Moiré and Its Application, 236-242 (Sept.).
Zachary, L.W. — Designing an All-purpose Force Transducer, 33-35 (Mar.).
Zero-shift Values of Automatic and Inexpensive Strain-gage Instrumentation Systems, 88-92 (Mar.).
Zalinka, J.J. — Fracture-toughness Tests and Displacement and Crack-stability Analyses of Tungsten Round Bend Specimens, 353-359 (Dec.).
Zhang, Y.P. — A Fully Automatic Stress Analysis System by Using Electo-optic Modulation, 344-347 (Dec.)

U.S. Postal Service

STATEMENT OF OWNERSHIP, MANAGEMENT AND CIRCULATION

(Required by 39 U.S.C. 3685)

1A. TITLE OF PUBLICATION	1B. PUBLICATION NO.	2. DATE OF FILING
EXPERIMENTAL MECHANICS	0 0 1 4 4 8 5 1	10-01-91
3. FREQUENCY OF ISSUE: Quarterly	3A. NO. OF ISSUES PUBLISHED ANNUALLY: 4	3B. ANNUAL SUBSCRIPTION PRICE: $72

4. COMPLETE MAILING ADDRESS OF KNOWN OFFICE OF PUBLICATION (Street, City, County, State and ZIP+4 Code) (Not printer): Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

5. COMPLETE MAILING ADDRESS OF THE HEADQUARTERS OF GENERAL BUSINESS OFFICES OF THE PUBLISHER (Not printer): Same as #4

6. FULL NAMES AND COMPLETE MAILING ADDRESS OF PUBLISHER, EDITOR, AND MANAGING EDITOR (This item MUST NOT be blank)

PUBLISHER (Name and Complete Mailing Address): K.A. Galione, Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

EDITOR (Name and Complete Mailing Address): Same as above.

MANAGING EDITOR (Name and Complete Mailing Address): N.E. Yergin, Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

7. OWNER (If owned by a corporation, its name and address must be stated and also immediately thereunder the names and addresses of stockholders owning or holding 1 percent or more of total amount of stock. If not owned by a corporation, the names and addresses of the individual owners must be given. If owned by a partnership or other unincorporated firm, its name and address, as well as that of each individual must be given. If the publication is published by a nonprofit organization, its name and address must be stated.) (Item must be completed.)

FULL NAME	COMPLETE MAILING ADDRESS
Society for Experimental Mechanics, Inc	7 School St., Bethel, CT 06801

8. KNOWN BONDHOLDERS, MORTGAGEES, AND OTHER SECURITY HOLDERS OWNING OR HOLDING 1 PERCENT OR MORE OF TOTAL AMOUNT OF BONDS, MORTGAGES OR OTHER SECURITIES (If there are none, so state)

FULL NAME	COMPLETE MAILING ADDRESS

9. FOR COMPLETION BY NONPROFIT ORGANIZATIONS AUTHORIZED TO MAIL AT SPECIAL RATES (Section 423.12 DMM only)
The purpose, function, and nonprofit status of this organization and the exempt status for Federal income tax purposes (Check one)

(1) [X] HAS NOT CHANGED DURING PRECEDING 12 MONTHS
(2) [ ] HAS CHANGED DURING PRECEDING 12 MONTHS (If changed, publisher must submit explanation of change with this statement.)

10. EXTENT AND NATURE OF CIRCULATION (See instructions on reverse side)	AVERAGE NO. COPIES EACH ISSUE DURING PRECEDING 12 MONTHS	ACTUAL NO. COPIES OF SINGLE ISSUE PUBLISHED NEAREST TO FILING DATE
A. TOTAL NO. COPIES (Net Press Run)	2600	2600
B. PAID AND/OR REQUESTED CIRCULATION 1. Sales through dealers and carriers, street vendors and counter sales	0	0
2. Mail Subscription (Paid and/or requested)	2148	2112
C. TOTAL PAID AND/OR REQUESTED CIRCULATION (Sum of 10B1 and 10B2)	2148	2112
D. FREE DISTRIBUTION BY MAIL, CARRIER OR OTHER MEANS SAMPLES, COMPLIMENTARY, AND OTHER FREE COPIES	32	31
E. TOTAL DISTRIBUTION (Sum of C and D)	2180	2143
F. COPIES NOT DISTRIBUTED 1. Office use, left over, unaccounted, spoiled after printing	420	457
2. Return from News Agents	0	0
G. TOTAL (Sum of E, F1 and 2—should equal net press run shown in A)	2600	2600

11. I certify that the statements made by me above are correct and complete. SIGNATURE AND TITLE OF EDITOR, PUBLISHER, BUSINESS MANAGER, OR OWNER: K.A. Galione, Publisher